



FEATURES

- Hydraulic angle change 30° left / right
- 25" diameter brush
- The brush hood covers 155°
- 4 and 5 foot broom widths
- Single pivot swing with CV joint
- Caster wheels follow ground contour

Lightweight attachment broom recommended for outfront mowers with mechanically driven mower deck with less than 25 hp.

SPECIFICATIONS

General

- Mechanically driven rotary angle broom
- Broom: 25" diameter x 5' wide (other widths available)
- Broom Speed: up to 200 rpm
- Storage stands

Frame

- Construction: 2-3/8" O.D. x .20" round tubular cross member; 2 brush arms (formed by 3/16" plate)
- Bearings: self aligned, greaseable flange

Drive

- Brush core: coupled to driveline by #50 roller chain
- Power: 7:1 worm drive gearbox with 1-1/8" output shaft

Brush

- Core: refillable flat wafers - poly, wire or combination (poly and wire combination on one wafer)
- Spacers and hubs: manufactured from 20 gauge mild steel strap 2" wide

Swing

- Hydraulic Angle Change: 30° left/right
- Swing pivot point inline with 50° CV joint

Brush Hood

- Construction: 16 gauge steel
- Coverage: 155°
- Formed edge fold for strength
- Predrilled for installation of deflector
- Ends covered by formed end plates

Brush Lift

- Provided by mower's deck arms

Finish

- One coat of epoxy primer and one polyurethane top coat
- MB yellow

Warranty

- Six month MB warranty policy

Available Options

- Dirt Deflector
- Sight Indicators (flags)
- Custom color

MB Companies, Inc. / www.m-bco.com / sales@m-bco.com

Attachments Division, Brush Replacements and Administration
1615 Wisconsin Ave., P.O. Box 200
New Holstein, WI 53061
Phone: 800-558-5800
Fax: 920-898-4588

Pavement Marking Equipment
79 Montgomery Street
Montgomery, PA 17752
Phone: 888-323-2900
Fax: 570-547-1629

Airport Snow Removal Products
1200 Park Street
Chilton, WI 53014
Phone: 800-558-5800
Fax: 920-849-2629