



FEATURES

- Hydraulic angle change 30° left / right
- 6, 7 and 8 foot broom width
- 32" diameter brush
- Parallel arm ground contour following system
- Two, 10" caster wheels
- The brush hood covers 155°
- Heavy duty spline shaft hydraulic motor.
Low flow, hi-torque motor available

Recommended for backhoe loaders, compact wheel loaders and tractor loaders. The parallel arm feature eliminates the operator's ability to apply down pressure. This allows the broom to follow ground contour.

SPECIFICATIONS

General

- Hydraulically driven rotary angle broom
- Broom: 32" diameter x 6' wide (other widths available)
- Broom Speed: up to 200 rpm
- Storage stands

Swing

- Hydraulic angle change: 30° left/right
- Arms: parallel top and bottom allow broom to "float"

Frame

- Construction: 3-1/2" O.D. x .30" wall thickness round tubular cross member; 2 brush arms (formed from 1/4" plate)
- Bearings: self aligned, greaseable pillow block

Drive

- Brush core: coupled to motors by 1" SAE B 6-spline shaft; splined hub on both ends of unit
- Power: one low-speed, high torque, 18 in³ motor
- Motor mount: outside the brush frame
- Motor guarded by 1/4" formed plate

Brush

- Core: refillable flat wafers - poly, wire, or combination (poly and wire combination on one wafer)
- Spacers and hubs: manufactured from 20 gauge mild steel strap 2" wide
- Broom removal: achieved without disconnecting hoses

Swing

- Hydraulic angle change: 30° left/right
- Arms: parallel top and bottom allow broom to "float"

Brush Hood

- Construction: 16 gauge steel
- Coverage: 155°
- Formed edge fold for strength
- Predrilled for installation of deflector
- Ends covered by formed end plates

Casters

- Two, 10" heavy duty, 360° swivel
- Allow for broom to follow surface contour
- Follow in in swept path

Brush Lift

- Provided by prime mover

Finish

- One coat of epoxy primer and one polyurethane top coat
- MB yellow

Warranty

- Six month MB warranty policy

Available Options

- Dirt Deflector
- Mechanical swing lock
- Electric / hydraulic swing system
- Sprinkler system
- Independent hydraulic system
- Hoses and couplers
- Sight indicators (flags)
- Fork lift bracket
- Bucket clamp
- Hydraulic flow divider / restrictor

MB Companies, Inc. / www.m-bco.com / sales@m-bco.com

Attachment Division, Brush Replacements and Administration
1615 Wisconsin Ave., P.O. Box 200
New Holstein, WI 53061
Phone: 800-558-5800
Fax: 920-898-4588

Pavement Marking Equipment
79 Montgomery Street
Montgomery, PA 17752
Phone: 888-323-2900
Fax: 570-547-1629

Airport Snow Removal Products
1200 Park Street
Chilton, WI 53014
Phone: 800-558-5800
Fax: 920-849-2629