

# Model 53H™

Tow Behind



(Shown with optional equipment - dirt deflector, strobe light, ridge tow hitch, fenders, light package, remote control)

## **FEATURES**

- Driven by towing vehicle hydraulic system
- Direct hydraulic motor brush drive eliminating chains and sprockets
- 7, 8 and 9 foot broom widths
- Hydraulic brush lift
- Easily reversible brush

***Recommended for towing vehicles that can supply a minimum of 15 gpm hydraulic flow.***

## **SPECIFICATIONS**

### **General**

- Length: 159"
- Width: 101" for 7' brush; 113" for 8' brush
- Height: 51"
- Weight: 1590 pounds
- Frame: 4" square tubular backbone and rectangular tube and plate rear frame

### **Brush**

- 7', 8' or 9' long x 32" diameter segmented wafer on steel core
- Poly, wire or combination
- 30° sweeping angle left/ right
- Drive: hydraulically by tow vehicle; low speed high torque gear type
- Frame: 3 1/2" O.D. x .30" wall tubular cross member

### **Brush Lift**

- Hydraulic using towing vehicle hydraulic system

### **Brush hood**

- 16 gauge steel
- Coverage: 155°

### **Wheels**

- Quantity: three
- 15" 8 ply radial
- Automotive type taper bearings

### **Tow Pole**

- Length: 60"
- Hitch: 3" pintle and safety chains

### **Finish**

- One coat of epoxy primer and one polyurethane top coat
- MB yellow

### **Warranty**

- Six month M-B warranty policy

### **Available Options**

- Lighting package (tail and signal lights)
- Rigid tow hitch
- Dirt deflector
- Sprinkler system
- Remote control
- Fifth wheel hitch
- Ball Hitch
- Strobe light
- Fenders

**MB Companies, Inc. / [www.m-bco.com](http://www.m-bco.com) / [sales@m-bco.com](mailto:sales@m-bco.com)**

**Attachments Division, Brush Replacements and Administration**  
1615 Wisconsin Ave., P.O. Box 200  
New Holstein, WI 53061  
Phone: 800-558-5800  
Fax: 920-898-4588

**Pavement Marking Equipment**  
79 Montgomery Street  
Montgomery, PA 17752  
Phone: 888-323-2900  
Fax: 570-547-1629

**Airport Snow Removal Products**  
1200 Park Street  
Chilton, WI 53014  
Phone: 800-558-5800  
Fax: 920-849-2629