

Model HT-R™

Tractor Mount



FEATURES

- Hydraulic angle change 30° left / right
- 5, 6, 7 and 8 foot broom widths
- 32" diameter brush
- Four point self centering swing system
- The brush hood covers 155°
- Heavy duty spline shaft hydraulic motor. Low flow, hi-torque motor available

Recommended for rear mount three point hitch applications with hydraulic capabilities of 8 gpm at 2,000 psi or more.

SPECIFICATIONS

General

- Hydraulically driven rotary angle broom
- Broom: 32" diameter x 6' wide (other widths available)
- Broom Speed: up to 200 rpm
- Complete with Category I or II three-point mounting hitch, hardware and storage stands

Frame

- Construction: 3-1/2" O.D. x .03" wall round tubular cross member; 2 brush arms (formed from 1/4" plate)
- Bearings: self aligned, greaseable pillow block

Drive

- Brush core: coupled to motors by 1" SAE B 6-spline shaft; splined hub on both ends of unit
- Power: one low-speed, high torque, 18 in³ motor
- Motor mount: outside the brush frame
- Motor guarded by 1/4" formed plate

Brush

- Core: refillable flat wafers - poly, wire or combination (poly and wire combination on one wafer)
- Spacers and hubs: manufactured from 20 gauge mild steel strap 2" wide
- Broom removal: achieved without disconnecting hoses

Swing

- Hydraulic angle change: 30° left/right
- Arms: maintain the center of the path on the center line of prime mover regardless of sweeping angle

Brush Hood

- Construction: 16 gauge steel
- Coverage: 155°
- Formed edge fold for strength
- Predrilled for installation of deflector
- Ends covered by formed end plates

Brush Lift

- Provided by three-point hitch
- Minimum ground clearance of 12" for transport

Finish

- One coat of epoxy primer and one polyurethane top coat
- MB yellow

Warranty

- Six month MB warranty policy

Available Options

- Dirt deflector
- Dual motors
- Sight indicators (flags)
- Sprinkler systems
- Reversing valve
- Hoses and couplers
- Independent hydraulic system
- Custom color

MB Companies, Inc. / www.m-bco.com / sales@m-bco.com

Attachments Division, Brush Replacements and Administration
1615 Wisconsin Ave., P.O. Box 200
New Holstein, WI 53061
Phone: 800-558-5800
Fax: 920-898-4588

Pavement Marking Equipment
79 Montgomery Street
Montgomery, PA 17752
Phone: 888-323-2900
Fax: 570-547-1629

Airport Snow Removal Products
1200 Park Street
Chilton, WI 53014
Phone: 800-558-5800
Fax: 920-849-2629