

Model TKH-T™

Tractor Mount



Shown with optional dirt deflector and independent hydraulic system.



FEATURES

- Hydraulic angle change 30° left / right
- 7, 8, 9, 10, 11 and 12 foot broom widths
- 32" diameter brush
- The brush hood covers 155°
- Heavy duty spline shaft hydraulic motors. Low flow, hi-torque motors available
- Broom head oscillation of 10 °

To be used on tractor's three-point system. This unit cannot have its own lift cylinder. Lift must be supplied by prime mover. Recommended for tractors with 90 or more horsepower.

SPECIFICATIONS

General

- Hydraulically driven rotary angle broom
- Broom: 32" diameter x 8' wide (other widths available)
- Broom Speed: up to 200 rpm
- Storage stands and flags

Frame

- Construction: 3-1/2" O.D. x .30" wall round tubular cross member; 2 brush arms (formed from 1/4" plate)
- Bearings: self aligned, greaseable pillow block
- Caster Wheels: Two, 16", mounted behind brush, rotate 360°
- 10° oscillating pivot to allow broom to follow ground irregularities

Drive

- Brush core: coupled to motors by 1" SAE B 6-spline shaft; splined hub on both ends of unit
- Power: two low-speed, high torque, 18 in³ motor
- Motor mount: outside the brush frame
- Motor guarded by 1/4" formed plate

Brush

- Core: refillable flat wafers - poly, wire or combination (poly and wire on one wafer)
- Spacers and hubs: manufactured from 20 gauge mild steel strap 2" wide
- Broom removal: achieved without disconnecting hoses

Swing

- Hydraulic angle change: 30° left/right
- Broom swings on a 1-1/2" center pivot

Brush Hood

- Construction: 16 gauge steel
- Coverage: 155°
- Formed edge fold for strength
- Predrilled for installation of deflector
- Ends covered by formed end plates

Brush Lift

- Provided by tractor's three point system

Finish

- One coat of epoxy primer and one polyurethane top coat
- MB yellow

Warranty

- Six month MB warranty policy

Available Options

- Dirt deflector
- Mechanical swing lock
- Electric/hydraulic swing system
- Sprinkler systems
- Hoses and couplers
- Hydraulic flow divider / restrictor
- Hydraulic oil cooler
- Reversing valve
- Custom color

MB Companies, Inc. / www.m-bco.com / sales@m-bco.com

Attachment Division, Brush Replacements and Administration
1615 Wisconsin Ave., P.O. Box 200
New Holstein, WI 53061
Phone: 800-558-5800
Fax: 920-898-4588

Pavement Marking Equipment
79 Montgomery Street
Montgomery, PA 17752
Phone: 888-323-2900
Fax: 570-547-1629

Airport Snow Removal Products
1200 Park Street
Chilton, WI 53014
Phone: 800-558-5800
Fax: 920-849-2629