

**MB Companies, Inc.**  
**MSV ATTACHMENT**

**MSV Angle Broom  
Specification**

- ◆ Sizes 60", 72" and, 96" brooms operate angled left, angled right, and straight positions.
- ◆ Three point Cat II hitch manufactured using box frame construction with tubular steel brush frame.
- ◆ Hydraulic angle change maximum 30 degrees left or right.
- ◆ Clearing width when fully angled for various sizes is as follows:
  - ❑ 60" broom clears 52" when angled 30 degrees
  - ❑ 72" broom clears 62" when angled 30 degrees
  - ❑ 96" broom clears 83" when angled 30 degrees
- ◆ Broom powered by dual 18 cubic inch, heavy duty spline shaft, high torque hydraulic motors.
- ◆ Broom diameter is 32 inches and available with poly, wire, or poly-wire combination bristles.
- ◆ Configured with 12 inch wide masticated rubber deflector strip.
- ◆ Broom controls integrated into vehicle joystick
- ◆ Four adjustable storage stands allows broom to be stored in convenient position for easy attachment and removal.
- ◆ Hydraulic connections made by quick disconnects
- ◆ Four point self centering swing system maintains the center of the swept path on the center of the vehicle.
- ◆ Brush hood covers 155 degrees and is formed from 16 gauge hot rolled steel



**MSV Sales**

1-800-558-5800 / [www.m-bco.com](http://www.m-bco.com) / [sales@m-bco.com](mailto:sales@m-bco.com)

1615 Wisconsin Avenue / P.O. Box 200 / New Holstein, Wisconsin 53061