

MB Companies, Inc.

MSV ATTACHMENT

Angle Plow Specification

- ◆ Sizes 50", 60", 72, 96" angle plows operate angled left, angled right, and straight positions.
- ◆ Maximum angle left or right is 30 degrees.
- ◆ Three point Cat I, Cat II hitch manufactured using box frame construction.
- ◆ Rolled moldboard is manufactured from 10 gauge hot rolled steel. Plow is configured with a spring loaded moldboard employing one set (2) or two sets (4) of coil extension springs.
- ◆ Clearing width when fully angled for various sizes is as follows:
 - ❑ 50" blade clears 43" when angled 30 degrees
 - ❑ 60" blade clears 52" when angled 30 degrees
 - ❑ 72" blade clears 62" when angled 30 degrees
 - ❑ 96" blade clears 83" when angled 30 degrees
- ◆ Dual, single acting, 2" bore cylinders provide hydraulic angling.
- ◆ Dual cushion valves to protect mold board
- ◆ Blade height is 32 inches.
- ◆ Configured with 6" wide masticated rubber deflector strip and replaceable ½" x 6" hardened cutting edge.
- ◆ Plow controls integrated into vehicle joystick
- ◆ Adjustable storage stand incorporated in hitch allows plow to be stored in convenient position for easy attachment and removal.
- ◆ Hydraulic connections made by quick disconnects
- ◆ Two cast iron adjustable, replaceable skid shoes mounted on outside corners of plow moldboard.



MSV Sales

1-800-558-5800 / www.m-bco.com / sales@m-bco.com

1615 Wisconsin Avenue / P.O. Box 200 / New Holstein, Wisconsin 53061