

MB Companies, Inc.

MSV ATTACHMENT

Folding V-Plow Specification

- ◆Folding plow to operate angled left, angled right, straight, in V-plow configuration and inverted V-plow (scoop) configuration.
- ◆Three point Cat I, Cat II hitch manufactured using box frame construction.
- ◆Rolled moldboard is manufactured from 10 gauge hot rolled steel. Each half is configured with a spring loaded trip edge employing dual compression springs.
- ◆Clearing width in straight configuration is 60". Clearing width is 50" in angled, V-plow, or inverted V-plow configurations.
- ◆Two dual acting, 2" bore pistons provide hydraulic angling.
- ◆Blade height is 33 inches.
- ◆Configured with two 5 inch wide masticated rubber deflector strips and two replaceable ½" x 6" hardened cutting edges
- ◆Plow controls integrated into vehicle joystick
- ◆Adjustable storage stand incorporated in hitch allows plow to be stored in convenient position for easy attachment and removal.
- ◆Hydraulic connections made by two sets of quick disconnects
- ◆Two cast iron adjustable, replaceable skid shoes mounted on outside corners of plow moldboard. Replaceable 10" center skid shoe with raised leading edge allows plow assembly to ride over cracks and small obstacles when operated in float mode.
- ◆Dual cushion valves to protect mold board
- ◆13 degrees of standard oscillation



MSV Sales

1-800-558-5800 / www.m-bco.com / sales@m-bco.com

1615 Wisconsin Avenue / P.O. Box 200 / New Holstein, Wisconsin 53061