



Airport Snow Removal Products

Model 3600-TRT

Conventional Tractor Mounted Runway Broom, 540 PTO



- Integrally mounted to a tractor having a recommended minimum 90HP or larger PTO drive
- 36" diameter @ 12, 14, and 16 foot broom lengths
- **347 rpm broom with 1655 ft-lbs of available torque at 5075 psi maximum working pressure**
- True free floating broom head hitch allowing broom to follow caster, not the tractor, to minimize brush pattern variation during operation.
- Hydrostatic broom drive utilizing the tractor's 540 RPM PTO connected to a speed increasing gear box driving a Sauer – Danfoss 90 series pump with variable speed control.
- Power transmitted to the broom core via fixed displacement “Low Speed - High Torque” motors connected to the broom core utilizing keyed tapered hubs to prevent any looseness in the connection for vibration concerns. Molded urethane drive cogs for torque transmission. Hardened steel pilot plates and core sprockets to support the radial loads.
- Includes rear three-point hitch mounted pump support, hydraulic reservoir and hydraulic oil cooler
- Broom oscillation of 10 degrees (+5, -5) permitting broom head tilt independent of tractor to compensate for surface variations to minimize brush pattern variation during operation.
- Entire broom head vibration analyzed as final “Quality Check” with report on vibration spectra (FFT plot)
- Optional rear mount air blower package available:
 - 7,483 cfm at 220 mph



M-B Companies, Inc. / Airport Snow Removal Products

1200 Park Street / Chilton, Wisconsin 53014

1-800-558-5800 / Fax: 920-849-2629 / sales@m-bco.com / www.m-bco.com

1/08

In the interest of continuous product improvement, M-B Reserves the right to change specifications without notice.