



Model CL-HT Trucks



Features

- Manual angle change 30° left / right.
- 3 foot broom width
- 32" diameter brush
- The brush hood covers 155°
- Heavy duty spline shaft hydraulic motor. Low flow, hi-torque motor available at no extra cost.

SPECIFICATIONS

General

- Hydraulically driven rotary pick up broom
- Broom: 32" diameter x 36" wide (other widths available)
- Broom Speed: up to 200 rpm

Frame

- Construction: 3-1/2" O.D. round tubular cross member; 2 brush arms
- Bearings: self aligned, pillow block

Drive

- Brush core: coupled to motors by 1" SAE B 6-spline shaft; splined hub on both ends of unit
- Power: one low-speed, high torque, 18 c.i.d. motor
- Motor mount: outside the brush frame

Brush

- Core: refillable flat wafers - poly, wire, or combination (poly and wire on one wafer)
- Spacers and hubs: manufactured from 20 gauge mild steel strap 2" wide
- Broom removal: achieved without disconnecting hoses

Swing

- Manual Angle Change: 30° left/right
- Swing on a 1-1/2 inch center pivot

Brush Hood

- Construction: 16 gauge steel

- Coverage: 155°

- Formed edge fold for strength
- Predrilled for installation of deflector
- Ends covered by formed end plates

Brush Lift

- Provided by single hydraulic cylinder with 3-1/4" stroke and 2 1/2" bore
- Minimum ground clearance of 12" for transport
- Adjustable chains set brush pattern

Finish

- One coat of epoxy primer and polyurethane
- Safety yellow

Warranty

- Six month MB warranty policy

Available Options

- Dirt Deflector
- Hydraulic swing cylinder
- Sprinkler Systems
- Independent hydraulic system
- Sight Indicators (flags)
- Remote control
- Auxillary hydraulic system with engine

M-B Companies, Inc.

E-mail: sales@m-bco.com ♦ www.m-bco.com

Power Brooms, Brushes, Wood Chippers

1200 Park Street
Chilton, WI 53014
Phone: 800-558-5800
Fax: 920-849-2629

Pavement Marking Equipment

79 Montgomery Street
Montgomery, PA 17752
Phone: 888-323-2900
Fax: 570-547-1629

Administration

1615 Wisconsin Ave., P.O. Box 200
New Holstein, WI 53061
Phone: 800-558-5800
Fax: 920-898-4588