



Model FLB

Skidsteer or Loaders



Features

- Quick and easy mounting hydraulic hook up and drive away
- Heavy duty spline shaft hydraulic motor low flow, hi-torque motor also available
- Bi-directional brush rotation
- 25" diameter brush
- 5, 6 and 7 foot broom widths

SPECIFICATIONS

General

- Hydraulically driven rotary pick-up broom
- Broom: 25" diameter x 72" wide (other widths available)
- Broom Speed: up to 200 rpm
- Complete with mounting hitch and hardware

Frame

- Brush Frame Construction: 14 gauge steel with 10 gauge side panels
- Bearings: self-aligning sealed ball bearings
- Wrap-around rubber drape

Drive

- Brush core: coupled to motors by 1" SAE B 6-spline shaft; splined hub on both ends of unit
- Power: at least one low-speed, high torque, 18 c.i.d. motor
- Splined hub: both ends of unit
- Motor mount: outside the brush frame

Brush

- Material picked up is carried over the brush or directly into bucket
- Core: refillable flat wafers - poly, wire or combination (poly and wire combination on one wafer)
- Spacers and hubs: manufactured from 20 gauge mild

steel strap 2" wide

- Broom removal: achieved without disconnecting hoses
- Brush Adjustment: threaded adjustment rods, located on each end of brush

Dump

- Hopper dumped using loader bucket dump function
- Broom has replaceable cutting edge

Brush Lift

- Provided by primer mover

Finish

- One coat of epoxy primer and polyurethane
- Safety yellow

Warranty

- Six month MB warranty policy

Available Options

- Dirt Deflector
- Sprinkler System
- Flow Divider
- Independent Hydraulic System
- Curb Broom (left or right)

M-B Companies, Inc.

E-mail: sales@m-bco.com ♦ www.m-bco.com

Power Brooms, Brushes, Wood Chippers

1200 Park Street
Chilton, WI 53014
Phone: 800-558-5800
Fax: 920-849-2629

Pavement Marking Equipment

79 Montgomery Street
Montgomery, PA 17752
Phone: 888-323-2900
Fax: 570-547-1629

Administration

1615 Wisconsin Ave., P.O. Box 200
New Holstein, WI 53061
Phone: 800-558-5800
Fax: 920-898-4588

In the interest of continuous product improvement, M-B Companies reserves the right to change specifications without notice. (9/04)