



# Model HT Tractors



## Features

- Complete mount package
- Hydraulic angle change 30° left / right.
- 5, 6, 7 and 8 foot broom widths
- 32" diameter brush
- Parallel arm swing system
- Electric/hydraulic control for lift and swing
- The brush hood covers 155°
- Heavy duty spline shaft hydraulic motor. Low flow, hi-torque motor available at no extra cost.
- Self contained independent hydraulic system
- Requires access to a PTO or front crankshaft pulley

## SPECIFICATIONS

### General

- Hydraulically driven rotary angle broom
- Broom: 32" diameter x 72" wide (other widths available)
- Broom Speed: up to 200 rpm
- Complete with mounting hitch and hardware and independent hydraulic system including pump, reservoir, electric over hydraulic controls for lift and swing

### Frame

- Construction: 3-1/2" O.D. round tubular cross member; 2 brush arms (formed from 1/4" plate)
- Bearings: self aligned, pillow block

### Drive

- Brush core: coupled to motors by 1" SAE B 6-spline shaft; splined hub on both ends of unit
- Power: one low-speed, high torque, 18 c.i.d. motor
- Motor mount: outside the brush frame

### Brush

- Core: refillable flat wafers - poly, wire or combination (poly and wire combination on one wafer)
- Spacers and hubs: manufactured from 20 gauge mild steel strap 2" wide
- Broom removal: achieved without disconnecting hoses

### Swing

- Manual Angle Change: 30° left/right
- Arms: maintain the center of the path on the center line of prime mover regardless of sweeping angle

### Brush Hood

- Construction: 16 gauge steel

### Coverage: 155°

- Formed edge fold for strength
- Predrilled for installation of deflector
- Ends covered by formed end plates

### Brush Lift

- Provided by single hydraulic cylinder with 3-11/16" stroke and 3" bore
- Minimum ground clearance of 12" for transport
- Threaded adjustment to allow flexibility within the application

### Controls

- Remote mounted electric over hydraulic valve system
- Basic valve includes a built in relief and valve for brush rotation, swing and lift
- Swing and lift hydraulics are on priority flow basis, directing .5 gpm from the brush rotation to swing or lift cylinder

### Finish

- One coat of epoxy primer and polyurethane
- Safety yellow

### Warranty

- Six month MB warranty policy

### Available Options

- Dirt Deflector
- Dual Motors
- Sight Indicators (flags)
- Storage Stands
- Sprinkler Systems
- Reversing Valve

## M-B Companies, Inc.

E-mail: [sales@m-bco.com](mailto:sales@m-bco.com) ♦ [www.m-bco.com](http://www.m-bco.com)

### Power Brooms, Brushes, Wood Chippers

1200 Park Street  
Chilton, WI 53014  
Phone: 800-558-5800  
Fax: 920-849-2629

### Pavement Marking Equipment

79 Montgomery Street  
Montgomery, PA 17752  
Phone: 888-323-2900  
Fax: 570-547-1629

### Administration

1615 Wisconsin Ave., P.O. Box 200  
New Holstein, WI 53061  
Phone: 800-558-5800  
Fax: 920-898-4588