



Model MLT-CT

Commercial Turf



Features

- Complete mount package
- Manual angle change 30° left / right
- 25" diameter brush
- The brush hood covers 155°
- 5, 6 and 7 foot broom widths
- Single pivot swing with TWO gearboxes to alleviate stress on CV joint

SPECIFICATIONS

General

- Mechanically driven rotary broom
- Broom: 25" diameter x 60" wide (other widths available)
- Broom Speed: up to 200 rpm
- Complete with mounting hitch and hardware

Frame

- Construction: 2-7/8" O.D. round tubular cross member; 2 brush arms
- Bearings: self aligned, pillow block

Drive

- Brush core: coupled to driveline by #50 roller chain
- Power: two 1.1:1 1" shaft, gearboxes, sprockets and shafts
- Installation: left or right end with no effect on sweeping

Brush

- Core: refillable flat wafers - poly, wire or combination (poly and wire combination on one wafer)
- Spacers and hubs: manufactured from 20 gauge mild steel strap 2" wide

Swing

- Manual Angle Change: 30° left/right
- Steel structure houses gearboxes and swing pivot point

Brush Hood

- Construction: 16 gauge steel
- Coverage: 155°
- Formed edge fold for strength
- Predrilled for installation of deflector
- Ends covered by formed end plates

Brush Lift

- Provided by prime mover's deck arms

Finish

- One coat of epoxy primer and polyurethane
- Safety yellow

Warranty

- Six month MB warranty policy

Available Options

- Dirt Deflector
- Storage Stands
- Hydraulic Swing Cylinder
- Sprinkler Systems
- Sight Indicators (flags)

M-B Companies, Inc.

E-mail: sales@m-bco.com • www.m-bco.com

Power Brooms, Brushes, Wood Chippers

1200 Park Street
Chilton, WI 53014
Phone: 800-558-5800
Fax: 920-898-4588

Pavement Marking Equipment

79 Montgomery Street
Montgomery, PA 17752
Phone: 888-323-2900
Fax: 570-547-1629

Administration

1615 Wisconsin Ave., P.O. Box 200
New Holstein, WI 53061
Phone: 800-558-5800
Fax: 920-898-4588

In the interest of continuous product improvement, M-B Companies reserves the right to change specifications without notice. (9/04)