



Model 53T

Tow Behind



Features

- Rear wheel drive provides power through ratchet and roller chains
- Two speed transmission plus neutral
- Hydraulic pump brush lift
- Balance springs permit brush to float as it sweeps
- Heavy 5" tubular main frame with 5" rear frame channel
- 3 1/2 " tubular brush frame

SPECIFICATIONS

General

- Length: 144" less tow pole
- Width: 91" for 84" brush; 103" for 96" brush
- Height: 50"
- Weight: 1600 pounds
- Frame: 5" channel rear frame and 5" tubular main frame

Brush

- 84" or 96" long x 32" diameter segmented wafer on steel core
- Poly, wire or combination
- 30° sweeping angle left/ right
- Balance springs to allow brush to float with surface contour
- Drive: traction driven via #80 chain from rear axle to transmission. Universal shaft to transmit power from transmission to #80 brush drive chain and sprocket
- Frame: 3 1/2" O.D. tubular cross member and reinforced end plates

Brush Lift

- Manual hydraulic pump and cylinder
- Safety lock for transport

Brush Hood

- 16 gauge steel
- Coverage: 120°

Wheel/ Hubs

- Quantity: three
- 15" 8 ply radial
- Automotive type

Tow Pole

- Length: 48"
- Hitch: 3" pintle and safety chains
- 2 - 3/8" O.D tubular steel

Finish

- One coat of epoxy primer and polyurethane safety yellow

Warranty

- Six month M-B warranty policy

Optional Equipment

- Dirt Deflector
- Ridgid tow pole
- Ball Hitch
- Lighting Package

M-B Companies, Inc.

E-mail: sales@m-bco.com ♦ www.m-bco.com

Power Brooms, Brushes, Wood Chippers

1200 Park Street
Chilton, WI 53014
Phone: 800-558-5800
Fax: 920-849-2629

Pavement Marking Equipment

79 Montgomery Street
Montgomery, PA 17752
Phone: 888-323-2900
Fax: 570-547-1629

Administration

1615 Wisconsin Ave., P.O. Box 200
New Holstein, WI 53061
Phone: 800-558-5800
Fax: 920-898-4588