



# Feed Bunk Sweeper Tractors



## Features

- Cleans round or square bottom fence -line styles
- Complete mount package
- 18 foot broom width
- Adjustable angle brush for different bunk widths
- Quick-attach to any category I and II thress point-hitch
- 32" diameter brush, poly, wire alternating or combination
- Hydraulic control for lift and swing
- Heavy duty spline shaft hydraulic motor. Low flow, hi-torque motor available at no extra cost.
- Requires access to a PTO or remote hydraulics

## SPECIFICATIONS

### Brush

- 32" diameter x 15" wide
- Adjustable angle
- Easy field replacment

### Drive

- Hydraulic motor
- Brush core: coupled to motors by 1" SAE B 6-spline shaft
- Power: low speed, high torque motor
- Recessed motor
- Hydraulic requirments: 10 GPM @ 1500 PSI

### Brush Speed

- 100 RPM @ 12 GPM

### Minimum Bunk Width

- 16" round or square bottom

### Mounting Frame

- Construction: welded rectangluar steel
- Brush Arm: spring centered with roller to follow bunk line contour

### Height Adjustment

- Brush arm chain adjustment for any bunk height

### Brush Hood

- Heavy steel deflector for operation protection

### Guide Marker

- Steel pipe marker attaches to tractor front for operator convenience

### Weight

- 475 pound shipping weight

### Finish

- One coat of epoxy primer and polyurethane
- Safety yellow

### Warranty

- Six month MB warranty policy

## M-B Companies, Inc.

E-mail: [sales@m-bco.com](mailto:sales@m-bco.com) ♦ [www.m-bco.com](http://www.m-bco.com)

### Power Brooms, Brushes, Wood Chippers

1200 Park Street  
Chilton, WI 53014  
Phone: 800-558-5800  
Fax: 920-849-2629

### Pavement Marking Equipment

79 Montgomery Street  
Montgomery, PA 17752  
Phone: 888-323-2900  
Fax: 570-547-1629

### Administration

1615 Wisconsin Ave., P.O. Box 200  
New Holstein, WI 53061  
Phone: 800-558-5800  
Fax: 920-898-4588