

Model MLT-LG™

Tractor Mount



FEATURES

- Hydraulic angle change 30° left / right
- 5, 6 and 7 foot broom widths
- 25" diameter brush
- The brush hood covers 155°
- Hydraulic lift for broom
- Single pivot swing with TWO gearboxes to alleviate stress on CV joint

Front mounted, mechanical drive recommended for compact utility tractors with 24-40 hp.

SPECIFICATIONS

General

- Mechanically driven rotary angle broom
- Broom: 25" diameter x 5' wide (other widths available)
- Broom Speed: up to 200 rpm
- Storage stands

Frame

- Construction: 2-7/8" O.D. x .20 wall round tubular cross member; 2 brush arms (formed by 1/4" plate)
- Bearings: self aligned, greaseable pillow block

Drive

- Brush core: coupled to driveline by #50 roller chain
- Power: two 1.1:1 1" shaft gearboxes, sprockets and shafts

Brush

- Core: refillable flat wafers - poly, wire or combination (poly and wire combination on one wafer)
- Spacers and hubs: manufactured from 20 gauge mild steel strap 2" wide

Swing

- Hydraulic angle change: 30° left/right
- Steel structure houses gearboxes and swing pivot point

Brush Hood

- Construction: 16 gauge steel
- Coverage: 155°
- Formed edge fold for strength
- Predrilled for installation of deflector
- Ends covered by formed end plates

Brush Lift

- Provided by single hydraulic cylinder
- Transport: Cylinder provides a minimum of 8 inches of ground clearance

Finish

- One coat of epoxy primer and one polyurethane top coat
- MB yellow

Warranty

- Six Month MB warranty policy

Available Options

- Dirt deflector
- Mechanical swing lock
- Sprinkler systems
- Sight indicators (flags)
- Custom color

MB Companies, Inc. / www.m-bco.com / sales@m-bco.com

Attachments Division, Brush Replacements and Administration
1615 Wisconsin Ave., P.O. Box 200
New Holstein, WI 53061
Phone: 800-558-5800
Fax: 920-898-4588

Pavement Marking Equipment
79 Montgomery Street
Montgomery, PA 17752
Phone: 888-323-2900
Fax: 570-547-1629

Airport Snow Removal Products
1200 Park Street
Chilton, WI 53014
Phone: 800-558-5800
Fax: 920-849-2629