

Model SMLT-CT™ Commercial Turf



FEATURES

- Hydraulic angle change 30° left / right
- 20" diameter brush
- The brush hood covers 155°
- 4 and 5 foot broom widths
- Single pivot swing with TWO gearboxes to alleviate stress on CV joint

Recommended for outfront mowers with mechanically driven mower deck with less than 25 hp. With heavy duty swing system and two gearboxes the SMLT-CT is by far the most robust broom in its class.

SPECIFICATIONS

General

- Mechanically driven rotary angle broom
- Broom: 20" diameter x 5' wide (other widths available)
- Broom Speed: up to 200 rpm
- Complete with mounting hitch, hardware and storage stands

Frame

- Construction: 2-3/8" O.D. x .20" round tubular cross member; 2 brush arms (formed by 1/4" plate)
- Bearings: self aligned, greaseable pillow block

Drive

- Brush core: coupled to driveline by #50 roller chain
- Power: two 1.1:1 1" shaft gearboxes, sprockets and shafts

Brush

- Core: refillable flat wafers - poly, wire or combination (poly and wire combination on one wafer)
- Spacers and hubs: manufactured from 20 gauge mild steel strap 2" wide

Swing

- Hydraulic angle change: 30° left/right
- Steel structure houses gearboxes and swing pivot point

Brush Hood

- Construction: 16 gauge steel
- Coverage: 155°
- Formed edge fold for strength
- Predrilled for installation of deflectors
- Ends covered by formed end plates

Brush Lift

- Provided by mower's deck arms

Finish

- One coat of epoxy primer and one polyurethane top coat
- MB yellow

Warranty

- Six month MB warranty policy

Available Options

- Dirt deflector
- Storage stands
- Mechanical swing locks
- Sprinkler systems
- Sight indicators (flags)
- Custom colors

MB Companies, Inc. / www.m-bco.com / sales@m-bco.com

Attachment Division, Brush Replacements and Administration
1615 Wisconsin Ave., P.O. Box 200
New Holstein, WI 53061
Phone: 800-558-5800
Fax: 920-898-4588

Pavement Marking Equipment
79 Montgomery Street
Montgomery, PA 17752
Phone: 888-323-2900
Fax: 570-547-1629

Airport Snow Removal Products
1200 Park Street
Chilton, WI 53014
Phone: 800-558-5800
Fax: 920-849-2629