



## P5000

### Airport Reversible Plow

The P5000 Plow can be retrofitted to many existing chassis and plow hitches, including DIN, hands-free, hustings, J-hook and pin type hitches. It is designed to provide a fully reversible left and right angle up to 32 degrees.

#### Features & Benefits

- DIN hitch standard
- Plow side hitch portion included; chassis side hitch not included
- Applicable to all MB chassis
- Retrofittable to existing chassis / plow hitches
- Fully reversible angle left and right up to 32 degrees
- 50 in moldboard height
- 65, 75, or 85 degree adjustable moldboard angle
- High visibility green polyethylene lined moldboard
- Straight moldboard blade
- 14 ft length
- Lift and swing uses chassis hydraulic system
- Requires two auxiliary hydraulic circuits on chassis
- Requires integral float in chassis hydraulics to allow plow to follow pavement independently
- Moldboard oscillation to follow angled (sway) pavement independent of chassis
- Two heavy-duty single casters to minimize shimmy and vibration, increase tire life
- Front mounted rubber deflector to reduce overspray for optimum operator visibility
- Consult MB prior to order to confirm size of plow and other options

#### Reversible Plow Options:

- ☐ Flared moldboard blade in place of straight moldboard blade
- ☐ Plow widths to 16, 18, 20, 22, and 24 ft
- ☐ Plow trip moldboard
- ☐ Hands free hitch with DIN chassis hitch
- ☐ Poly, carbide, Kueper and tungsten carbide inserted rubber cutting edge in place of steel cutting edge available in each length of plow

#### Reversible Plow Spare Parts:

- ☐ Caster tire and wheel
- ☐ Caster tire, wheel, hub, bearings, axle and nuts
- ☐ Caster tire and wheel, foam filled
- ☐ Caster tire, wheel, hub, bearings, axle and nuts, foam filled
- ☐ Poly, carbide, Kueper and tungsten carbide inserted rubber cutting edges available in each length of plow.

